30th St. 3000 N OFFICE OF THE MARION COUNTY SURVEYOR SECTION RECORD CORNER  $\geq$ SECTION 27 TOWNSHIP 16 RANGE 3 DATE: 10-31-03 140 Wilcoxen PARTY CHIEF: \_\_\_ CREW: \_ (1) TYPE OF MARKER: Harrison Harding METHOD OF ESTABLISHMENT: County: 10-30-98 IN. S.P.C. E ZONE NAD '83 16032702 506551.6971(m) NAME: N: E: 55387.0166(m) 2. 3. 109.07 <u> 30th Street 3000 N</u> 4.

Original post set 1820 by Laughlin with witness: 14" beech S 55 E 20 links, 12" dogwood N 11 W 18 links per Marion County Atlas pg. 7. Hosbrook 7-8-1851 called no stone and one green witness per Center Township Legal Survey Book pg. 9. Cleveland 3-25-81 called PK nail. Cleveland 1-1-86 called railroad spike set. Kiste 8-13-96 called railroad spike. Excavated 10-30-98 by Wilcoxen set Harrison in accordance with 30th Street Construction project. 16032702

10032702		
REF.	DISTANCE	DESCRIPTION
1.	28.02'	Mag nail w/brass washer E PwP#54-432 A 6"up
2.	76.40	SW corner "Givens Hand Car Wash" . 1402 W. 30th
3.	109.07'	SE corner
4.	78.33	Face of corner steel fence post